Philips
Component video cable

10 m

SWV6315

Enjoy the ultimate viewing experience

Take your components to optimum performance. This top of the line cable offers the best connection for transferring video signals between components.

Enjoy better picture quality
- 24 carat gold-plated connectors optimize signal
- 4-Cut connectors for secure connections
- 99.97% Oxygen-Free Copper (OFC)
- Split center pin for better signal transfer

Protects against signal loss
- 100% aluminum shielding
- Copper braided shielding

Easy installation
- Color coded connectors for instant recognition
- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability
- Heavy-duty brass shell for extended durability
- Super pliable jackets for outstanding flexibility

PHILIPS
sense and simplicity

Component video cable
10 m

SWV6315/10

Specifications

Inner Carton
- EAN/UPC/GTIN: 87 12581 31463 7
- Quantity: 2
- Gross weight: 5.28 kg
- Tare weight: .28 kg
- Net weight: 5 kg
- Length (cm): 35 cm
- Width (cm): 24.5 cm
- Height (cm): 27.5 cm

Outer Carton
- EAN/UPC/GTIN: 87 12581 31464 4
- Quantity: 4
- Gross weight: 11.52 kg
- Tare weight: .94 kg
- Net weight: 10.58 kg
- Length (cm): 50 cm
- Width (cm): 37 cm
- Height (cm): 29 cm

Packaging
- EAN/UPC/GTIN: 87 12581 31462 0
- Quantity: 1
- Gross Weight: 2.5 kg
- Tare Weight: .1 kg
- Net Weight: 2.4 kg
- Height: 12 cm
- Length: 33 cm
- Width: 25 cm

Product highlights

Color-coded connectors
Color coded connections make it easy to install your cable into the correct inputs and outputs

24 carat gold-plated connector
24 carat gold-plated connectors ensure the best signal quality for your components.

100% aluminum shielding
This protective layer of aluminum guards against electromagnetic interference for improved signal quality.

Copper braided shielding
This protective layer of copper blocks radio frequency interference for improved signal quality.

4-Cut connectors
4-Cut connectors ensure secure connections between your component and your cable.

99.97% OFC solid conducter
99.97% Oxygen-free copper (OFC) cable core provides optimum signal quality.

Split center pin
The split center pin allows for better signal transfer and an improved connection to the component inputs.

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play
Plug and play offers easy installation of components without time-consuming installations.

Heavy-duty brass shell
The heavy-duty brass shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Super pliable jackets
Super pliable PVC jackets are abrasion-resistant for outstanding flexibility and protection against everyday wear and tear.

Issue date 2008-03-13
Version: 2.0.4
12 NC: 8670 000 26832
EAN: 87 12581 31462 0

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com